



Overview

Model Name	APC Back-UPS 1100VA, 230V, AVR, Argentina
Includes	Telephone Cable , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Argentina

Output

Output Power Capacity	660 Watts / 1100 VA
Max Configurable Power (Watts)	660 Watts / 1100 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz
Output Frequency (sync to mains)	Line Interactive
Output Connections	(6) Australian (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	Australian/Chinese
Cord Length	1.16 meters
Input voltage range for main operations	150 - 280 V
Maximum Input Current	5 A
Input Breaker Capacity	10 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 hour(s)
Replacement Battery	APCRBC113
RBC Quantity	1

Communications & Management

Interface Port(s)	USB
Available SmartSlot™ Interface Quantity	0
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	273 joules
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)

Physical

Maximum Height	215.0 mm
Maximum Width	130.0 mm
Maximum Depth	336.0 mm
Rack Height	0 U
Net Weight	12.0 kg
Shipping Weight	12.92 kg
Shipping Height	295.0 mm
Shipping Width	245.0 mm
Shipping Depth	440.0 mm
Master Carton Units	2.0
Master Carton Dimensions (Length x Width x Height)	20.0 inches
Master Carton Weight	25.86 kg
SCC Codes	1073130429136 4
Units per Pallet	24.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-9000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	IRAM
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs