

DHI- XVR7808/16S

8/16 Channel Penta-brid 1080P 2U Digital Video Recorder



- Embedded processor
- H.264+/H.264 dual-stream video compression
- Support HDCVI/AHD/TVI/CVBS/IP video inputs
- Max 12/24 channels IP camera inputs, each channel up to 5MP
- Max 48/96Mbps Incoming Bandwidth
- Smart Search and Intelligent Video System



System Overview

Dahua, as a technology leader, is always the first ever developed the shining new technology in the security industry ,and today we present XVR. As the perfect solution to upgrade existing video surveillance systems, XVR supports penta-brid access technology such as HDCVI, AHD, TVI, CVBS and IP to effortlessly integrate with popular industry formats, offering an affordable solution loaded with flexible options.

Designed as a full compatibility product, XVR is able to provide end user the simplicity of analog system, namely lower system cost, simple installation and use of existing cable. It is ideal for a wide range of applications such as public safety, retail store, transportation, home protection and education.

Functions

Smart H.264+

Smart Codec, H.264+ can reduce up to 70% bit rate and storage requirements without having to invest in new cameras.

HDCVI/ AHD/TVI/CVBS Auto-detect

The XVR can auto recognize the signal of front-camera without any setting. It makes operation more friendly and convenient.

5MP Resolution

The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing.

Spot Output

It is made for a secondary monitor. This allows the operator to view one special monitor that assigned to selected cameras or video inputs from higher security areas.

Intelligent Video System (IVS)

With built-in intelligent video analytics, the XVR has the ability to detect and analyze moving objects for improved video surveillance. The XVR provides optional standard intelligence at the edge allowing detection of multiple object behaviors such as abandoned or missing objects. IVS also supports Tripwire analytics, allowing the camera to detect when a pre-determined line has been crossed.

Face Detection

It is a type technology being used in a variety of applications that search or identify individuals which show front cameras.

Smart Search

This function helps you get more motion detect video during a short time through drawing a region when playback. It is very useful when an emergency occurs.


Technical Specification		Audio and Video	
System			
Main Processor	Embedded Processor	HDCVI Camera Input	8/16 Channel
Operating System	Embedded LINUX	IP Camera Input	8+4/16+8 Channel, each channel up to 5MP
Display		Audio In/Out	8/16 Audio In, 1 Audio Out, BNC
Interface	2 HDMI, 1 VGA, 1 TV	Two-way Talk	1 Mic In, 1 Mic Out, BNC
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	Recording	
Multi-screen Display	8CH: 1/4/8/9/16 16CH: 1/4/8/9/16/25	Compression	H.264+/H.264
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	Resolution	1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF
Video Detection and Alarm			
Trigger Events	Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips	Record Rate	Main stream: 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps) Sub stream: D1/CIF/QCIF(1~25/30fps)
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis	Bit Rate	1Kbps ~ 6144Kbps Per Channel
Alarm input	16	Record Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Relay Output	6	Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec
Playback and Backup			
Playback	8CH: 1/4/9 16CH: 1/4/9/16	Network	
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second), Smart search	Interface	2 RJ-45 Port (1000M)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom	Network Function	HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search (Support Dahua IP camera, DVR, NVR, etc.)
Backup Mode	USB Device/Network	Max. User Access	128 users
Storage			
Internal HDD	8 SATA Ports, up to 8TB capacity for each disk	Smart Phone	iPhone, iPad, Android
eSATA	1 Port	Interoperability	ONVIF 2.42, CGI Conformant
Auxiliary Interface			
USB	4 USB Ports (2 USB 2.0, 2 USB 3.0)	Electrical	
RS232	1 port, for PC communication & Keyboard	Power Supply	AC100V-240V, 50/60Hz
RS485	1 Port, for PTZ Control	Power Consumption	<35W (Without HDD)
RS422	1 Port, for PTZ Control	Environmental	
Third-party Support			
Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more	Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 0~ 90% RH
		Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0~ 90% RH
Construction			
Dimensions	2U, 440mm×455mm×95mm (17.3" x 17.9" x 3.7")		
Net Weight	6.5kg (14.32 lb) (without HDD)		
Gross Weight	9.8kg (21.6lb)		
Installation	Desktop installation/Rack-mounted		
Certifications			
Certifications	FCC: Part 15, Subpart B: 2015		
	CE: EN 55032:2015(Class B), EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014, EN 61000-3-2:2014, EN61000-3-3:2013		
	UL:EN60950-1:2006 + A1:2010 + A11:2009 + A12:2011 + A2:2013		

Ordering Information


Type	Part Number	Description
8/16 Channel XVR	DHI-XVR7808S	8 Channel Penta-brid 1080P 2U Digital Video Recorder
	DHI-XVR7816S	16 Channel Penta-brid 1080P 2U Digital Video Recorder

Rear Panel

DHI-XVR7808S



DHI-XVR7816S



Dimensions (mm)

